







Clearline Qompact roller shutters provide a complete system that increases security, prevents break-ins and protects against the elements. The very small roller shutter box measuring just 16.5 cm at an element height of 2.60 m enables elegant solutions.

## Unobtrusive

# **Hurricane tested**

Florida (FBC) hurricane approvals. In fact, Qompac 6000mm(19.5ft) wide.

#### Colours

Clearline shutters can be individually powder coated

#### Product service life.

All roller shutter components are designed for long service

#### **Motor and controls**

RDS motors and controls. The award winning Somfy system

### **Available standard colours**




RAI

RAL 9006 9016

Special colours in Ral for an extra charge.

#### Strong and Compact

Traditional roll shutters require a large 10"-12" (250 mm - 300 mm) housing, ruining the style and look of your home. Now, with the Qompact shutter system, an 84" (2,1 m) tall opening will require only a compact 6" (150 mm) housing. That is 40-50% smaller, creating a much more appealing installation.



# Strong


Qompact combines premium design with unparalleled strength. The single-walled, extruded slats withstand sledge hammer impacts and hurricane impact tests.


In head-to-head tests, Qompact outperformed its foam-filled competitors every single time.



In impact testing, Qompact withstood 82 punches, 5 kicks, and 80 hits with a sledge hammer. The foam-filled shutter was destroyed in seconds.







Extruded aluminium Q profile, example profile no. 4

#### Box types








#### Box sizes = element heights with aluminium Q profile

= Element height 2.10 m
= Element height 2.60 m
= Element height 3.00 m
= Element height 3.60 m

Max. element height 3.60 m, max. element width 4.60 m

### 25 % smaller box:

- Tront-mounted roller shutters with aluminium profile CD 150 ultra (40 mm profile), foam core, element height 2.10 m, box 205 mm
- Qompact roller shutters with extruded aluminium Q profile = element height 2.10 m, box 150 mm 25% smaller box





# **End Retention**

End retention screws (shown below) keep the curtain captive in the rails. Qompact curtains can't be pried out with crowbars or pushed out of the rails due to high winds.

Note: Qompact
can also be
made without
end retention
where smaller
siderails are sufficient.





Qompact's end retention prohibits the curtain from being pushed out of the rails. Without end retention, the 40mm foamfilled curtain was easily compromised.

# **Hinge Strength**

The improved slat design is 27-times stronger than a perforated 40mm slip hinge, making a Qompact shutter impenetrable by comparison.



Pull-Apart Strength Test with 152mm (6in.) Sample. Qompact Pull Apart at 8050 kg/m 40mm Pull Apart at 296 kg/m

#### **Hurricane Tested**

Qompact shutters meet the strict standards for U.S. Florida (FBC) hurricane approvals. In fact, Qompact passed with 330 km/h (200 mph) winds up to 6000mm (19.5 ft) wide.





# **ALTUS®**Radio Controlled Motor

#### Description

Altus® is suitable for pre- and post-construction opportunities and can be controlled with any Radio Technology Somfy accessory including hand-held remote controls, wireless wall switches and timers.

#### **Benefits**

#### **Comfort & Convenience**

- Long range remote control doesn't require direct line of sight.
- Smartphone and tablet app available for quick and easy control even while away.

#### **Energy Savings**

- Motorized rolling shutters can reduce heat gain in the summer and heat loss in the winter by up to 40%.
- Motorized retractable awnings can reduce heat gain in the summer by 77% while in use. Motorized exterior screens can potentially block up to 90% of solar rays.

#### **Protection**

- Motorized rolling shutters provide a rigid protective barrier for your home, resistant to manual lifting. In addition, they protect your home from storm damage.
- Motorized retractable awnings and exterior screens not only shield your family from the sun, but offer a cool, comfortable outdoor living space.









